



NO.	SYMBOL	NO.	SYMBOL	NO.	SYMBOL	NO.	SYMBOL	NO.	SYMBOL
1	Q1	16	Q4	31	R3	46	SEL1		
2	K2	17	B5	32	R4	47	SEL2		
3	A2	18	B6	33	R3	48	VDD		
4	A1	19	B7	34	R6	49	VCI		
5	GND	20	Q4	35	R7	50	NC		
6	NC	21	Q1	36	SEN	51	NC		
7	NC	22	Q2	37	HIS NC	52	NC		
8	RES3	23	Q3	38	VSW NC	53	NC		
9	CS9	24	Q4	39	SDCLK	54	NC		
10	SOX	25	Q5	40	SHIT	55	NC		
11	S01	26	Q6	41	T8	56	GND		
12	B0	27	Q7	42	REV	57	X1		
13	B1	28	Q8	43	RL	58	Y1		
14	B2	29	Q1	44	SEL0	59	X2		
15	B3	30	Q2	45	SEL0	60	Y2		

Specification:
 1. Display mode: TN(TFT)/Negative/Transmissive
 Logic power supply voltage=2.8V
 2. Viewing angle: 6 O'Clock
 3. Operating temp: -20° C~+70° C
 Storage temp: -30° C~+80° C
 4. Drive IC: HX8238-A
 5. Connection type: COG+FPC
 6. Unspecified tolerance is ± 0.3mm
 7. ROHS request

		UNIT		SCALE		MODULE NO.	EDG350A02TXOGA	LCD No.	AMX-2539-AOCM						
		mm	A4	FIT	2007-11-25	DESIGNED		2007-11-25	CHECKED	2007-11-25	VERIFIED	2007-11-25	APPROVED	2007-11-25	FILE NAME
		mm	A4	FIT	2007-11-25	DESIGNED	2007-11-25	CHECKED	2007-11-25	VERIFIED	2007-11-25	APPROVED	2007-11-25	FILE NAME	Count. Drawing